8CH 5-in-1 HD DVR



Model:SV-ADVR7008B-MH-E

Product name: 8CH 2HDD 5-in-1 HD DVR

Features:

- One step on the Internet, wizard settings, auto search IP Device, very easy to operate.
- AHD TVI CVI CVBS IP 5-in-1
- Video compression H.264
- Support VGA HDMI
- Video input :

(Analog):8*1080P@12fps;8*1080N (Hybrid):4*1080P(Analog)+4*1080P(IP); (IP) 4*5M;4*3M;8*1080P+8*960P;16*960P

- Support **2SATA(Up to 6TB for each disk)**, 2*USB2.0 port port
- Stronger network service. support IE browse and CMS software
- Support Chinese, Russian, English, Italian, Portuguese, Spanish, French, German 30 language
- Support ONVIF, Support Third-party network cameras;
- Support Web, CMS, platform management software MYEYE, Provide SDK;
- Support cloud service, network penetration, alarm information pushed to phone ,etc;
- Support multiple network services like DHCP, FTP, DNS, DDNS, NTP, UPNP, EMAIL, 3G, WIFI, IP searches, Alarm Center, etc.

Specification

	Model	SV-ADVR7008T-MH-E
	Main processor	Hi3521A
System	Operating System	Embedded Linux
	System Resources	Simultaneous multi-channel real-time recording, playback, network
Operat	Operator	16-bit true color graphic menu operation interface, support mouse
or	Preview	1/4/8
	Video standards	PAL(625TVL,50f/s);NTSC(525TVL,60f/s)
	Video	H.264
	Display quality	VGA,HDMI
Video	Playback quality	5M/1080P/960P/720P
Audio	Video in	(Analog):8*1080P@12fps;8*1080N
		(Hybrid):4*1080P(Analog)+4*1080P(IP);
		(IP) 4*5M;4*3M;8*1080P+8*960P;16*960P
	Motion detection	Support
	Audio	G.711a
	intercom	Support
Record	Recording mode	Manual>Alarm>Video Detection>Continuous
	Local Playback	8CH
Storage	Search mode	search by Time/calendar/event/channel
&	Space Occupation	Video:CIF 4~5G/ day*channel, D1 8~10G/ day*channel, 1080P ~40G/
		day*channel; audio:691.2M/ day*channel
	Record Storage	HDD or network
	Backup mode	Network backup, USB hard disk, USB burner, SATA burner
	Video input	8*BNC interface
	Video output	1ch VGA, 1ch HDMI HD output
	Audio I/O	1/1
	Alarm I/O	0/0
	Network interface	1*RJ45 10M/100M
	USB interface	2*USB2.0 port port
	Hard disk	2SATA(Up to 6TB for each disk)
Other	ONVIF	Support
	Power supply	12V/3A
	Power	<10W(Without HDD)
	Temperature	0°C-+55°C
	Humidity	10%-90%
	Atm	86kpa — 106kpa
	dimension	mm(H)* mm(W)