

32CH 5MP 8HDD H.265 HD NVR

Key Features



- Support VGA, HDMI 4K output ;
- Support web, CMS, center platform management software MYEYE,provide SDK development;
- Support multiple cloud technology, network penetration, alarm information pushed to your phone and other functions;
- Support multiple network services (support DHCP, FTP, DNS, DDNS, NTP,UPNP, EMAIL, 3G, WIFI, IP searches, Alarm Center, etc.);
- Visit remotely,built-in ARSP,achieve star up by one step

Technical parameters

Model	SV-NVR8032K-Q
System	
Main processor	Hi3536
Operating System	Embedded Linux
System resources	Simultaneous multi-channel real-time recording, playback, network operation, USB backup
Interface	
Operator interface	16-bit true color graphic menu operation interface, support mouse operation
Preview	1/4/8/16/24/32
Video	
Video input (IP)	8*4K/32*5M/16*3M
Access bandwidth	384Mbps
Forwarding bandwidth	307Mbps
Video compression	H.265/H.264
Display quality	Max:4K
Playback quality	4K/5M/3M
Decode	2*4K/4*5M/8*3M
VR	unsupport
Motion detection	Support(depend on camera)
Audio	
Audio compression	G711A
Intercom	support
Record and playback	
Record mode	manual>alarm>motion detection>timing

Local playback	2*4K/4*5M/8*3M
Search mode	Search by Time/Calendar/Event/Channel
Storage and Backup	
Record storage	HDD、Network
Backup mode	Network backup, USB hard disk, USB burner, SATA burner
External interface	
Video output	1ch VGA, 1ch HDMI HD output
Audio I/O	1/1
Alarm I/O	16/4
Network interface	RJ45 10M/100M self-adaptive Ethernet port
USB interface	1*USB2.0 port,1*USB3.0 port (Reserved 2 pre interface)
HDD	8*SATA(Up to 8TB for each disk)
General	
PTZ control	Control PTZ device by network
ONVIF	Support
Power supply	ATX
Power Consumption	<10W(Without HDD)
Work environment	Temperature:0℃-+55℃ , Humidity:10%—90%RH , Atm:86kpa—106kp
Dimension	L443*W427.5*H92MM
Weight	6.0KG

Interface Description

