

- One-step remote monitoring can be worked well based on cloud service, simple operation steps ensures plug and play.
- Embedded wifi module, support 802.11b/g/n protocol, 300Mbps ensures short time delay for 4/8ch 2.0MP input.
- IP Camera auto connecting based on wireless technology, simple installation without IP cable arranging.
- > Plug and play, picture shows automatically when power turned on.
- Professional security wifi module with strong signal penetration ability, max distance can reach to 1000M.
- > Support remote monitoring for phone(iPhone,Android), PAD, PC.
- > Support video viewing, playback, backup.
- USB multiplexing technology support USB mouse, backup, upgrading.
- Support VGA and HDMI output simultaneously, HDMI for 2.0MP max.
- Strong network service(DHCP, PPPOE, DNS, NTP, UPNP, IP search), complete support (WEB, SDK), customized service can support.
- > Unique watch dog function ensures circuit protection.

Technical parameters

Model	SVN-NK08WH6200	
NVR parameters		
System		
Main processor	MSR630Q	
Operation System	Embedded LINUX	
system resource	Simultaneous multi-channel real-time recording, real-time playback, multi-channel multi-person	
	network operation, USB backup	
Interface		
Operation interface	24-bit true color graphical menu interface with mouse operation	
Picture Display	1/4/6/8/9	
Image coding	BaseLine Profile / Main Profile / High Profile	
Playback Quality	1080P/960P/720P/960H/D1/360P/VGA	
Video Input	8ch 2.0MP	
Motion Detection	396 (22*18) detection areas can be set per screen; sensitivity can be set	
Audio		



Audio compression	G711.A,G711.U		
monitor	Support		
Recording Type	Video and playback		
	Manual, Timing, Motion detection, Alarm		
Playback	Max 4ch 2.0MP		
Recorder Check	Time/date/issue/channel search		
Backup Type	USB, removable hard disk		
Interface			
Video Output	1ch VGA, 1ch HDMI		
Audio Output	1ch		
Ethernet	1*RJ45 10M/100M auto adjustable		
USB Interface	2*USB2.0		
SATA	1 (Max.6T)		
Antenna	2CH 150Mbp Antenna		
General			
Power Supply	DC 12V 2A		
Net Weight	1.0Kg(Without hard disk)		
Working Humidity	10%-90%		
Working Temperature	-10°C-+55°C		
Dimension	483*89*433mm		
WiFi IPC			
Effective Pixels	2.0MP,1920(H)*1080(V)		
Sensor	1/27" CMOS		
Min. Illumination	Color:0.05Lux@F1.2; B/W: 0.01Lux@F1.2		
Electronic Shutter	NTSC: 1/301/10000S; PAL: 1/251/10000S		
Day/Night Switch	ICR		
Video compression	H.265		
H.265 Coding type	PROFILE_BASELINE		
Image Format	1920*1080 (1080P)		
Frame Rate	50Hz:15fps/60Hz:15fps		
Privacy Mask	4 area		
Image Setting	brightness/ contrast/ saturation/gain/ shutter/ white balance		
Day/Night	Support		
Smart Alarm	motion detection/shelter alarm/IP cable no connection/IP address conflict		
Protocol	TCP/IP, DHCP, HTTP, HTTPS, NTP, DNS, RTP, RTSP		
General Function	double stream/ heartbeat/ mirror/ shelter / anonymous access		
Ethernet	1*RJ-45 (10/100Base-T)		
Wifi Antenna	Support 8188EUS, etc.		
Lens	4mm		
	DC12V 1A		
Power Supply			
Power Consumption	≤6W		
Working Environment	-10°C~50°C,30%~80%RH		
Dimension	175(L)*66(W)*66(H)mm		
Net Weight	500g		

Packing List

WiFi IP Camera*8
SCH WiFi NVR*1
Netwotk Cable Line*1
Mouse*1
CD dish*1
Quick Installation Guide*1
Screws

8.product display:





