

Outdoor Wifi 4G Sim Card Ip Camera

Key Features



- 2.0Megapixel. 1080P.
- 2.8-12mm auto iris lens,
- IR view distance: 50m(2pcs 42mil array leds)
- Motion detection, email alert, FTP upload
- Iphone, 3G phone, Smartphone supported
- Multi-language, Firefox, Safari, Google browser
- Built-in IR Cut,No Color Cast.
- P2P, PNP: Plug&play, Support QR code scanning to view on Iphone and andriod Mobiles
- No need to connect power adaptor, not only security, but also energy saving.
- when temperature of the sunshine keeps higher than 33°C,the battery can work Continuously.
- Support SIM card ,3G/4G.
- Support TF Card slot max 64GB

Technical parameters

Model	SVN-WH3820WG
Camera	
Image Sensor	1/2.8" SONY323 low lux CMOS
Resolution	1080P/1920*1080
Lens	2.8-12mm
IR Distance	50 Meters at most
Min. illumination	Color : 0.01Lux/F1.2; B/W : 0.001 Lux/F1.2
Infrared LED	2pcs array IR LEDs
IR Cut filter	Auto
TF Card Support	Max 64Gb
Network	
P2P	Yes
Onvif	Yes
Video Processing	H.264, dual stream, AVI format, 0.1M ~8Mbps bit rate adjustable
Frame Rates	support 1~30fps adjustable
Network	1* RJ45,10/100M, Support RTSP/FTP/PPPOE/DHCP/DDNS/NTP/UPnP/SMTP
4G	
4G standard	FDD-LTE
Frequency range	B1(2100MHz), B3(1800MHz), B7(2600MHz), B8(900MHz), B20(800MHz)
Transmission Rate	Upload max:50Mbps, download max: 150Mbps
Security	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK

3G	
3G standard	WCDMA
Frequency range	B1(2100MHz), B8(900MHz)
Transmission rate	Upload max:5.76Mbps, download max: 21Mbps
Security	WEP, WPA/WPA2, WPA-PSK/WPA2-PSK
General	
Power Requirement	DC12V 2A
Waterproof Level	Waterproof IP66
Material	Aluminum
Installation	Rack mounting
Operating Temperature	-10° C -- +60° C
Operating Humidity	10%~90%
Dimensions	185x93x62(mm)
Pack Dimensions	215x155x105(mm)
Pack weight	1.0KG

