



Key Features

- Support network control mode, with independent IP address;
- Supporting Onvif Protocol to PTZ Control;
- 5" industrial LCD screen, resolution 800*480, image decoding, real-time monitoring;
- Can directly control the camera to rotate in all directions, zooming and zooming the lens, and variable speed control according to the strength of the joystick control;
- It has the shortcut key operation of set cruise, transfer cruise, set scan, transfer scan, set watch, transfer watch, etc;
- Support custom function buttons, you can add shortcut function (need to be customized);
- Knob function is designed to achieve the pan/tilt speed and zoom speed adjustmen.

Feature

This network control keyboard with decoding function, has strong maneuverability and effectively solves the problem of inaccurate and inconvenient mouse click control, unique surface hardening can effectively prevent scratching, 5 inch LCD screen display is excellent, image decoding experience is better.

It supports the standard Onvif protocol. It has good compatibility, strong scalability, and easy operation, only takes a few steps to achieve perfect control of the network ptz camera.

Technical parameters

Model	SV-KB630IP
Input Voltage	DC12V/2A
Interface	RS422,RS232,Netwrok,Power interface
Key	Silicone button
Display mode	5-inch Industrial Screen
Prompt tone	Keyboard sound prompt on/off
Power Consumption	0.6W max
Protocol	Supporting Onvif Protocol
Operation Temperature	0°C~55°C / 14°F~131°F

Operation Humidity	20%-80% RH, Non-condensation
Storage Temperature	-10°C~60°C / 14°F~140°F
Storage Humidity	0-90% RH, Non-condensation
Size	297mm*210mm*126mm

