



NVR2200C-P Series				
Model		SV-NVR2204C-P4/JN	SV-NVR2208C-P8/JN	SV-NVR2216C-P8/JN
OS		Embedded Linux		
Video&Audio input	Incoming bandwidth	40Mbps	80Mbps	80Mbps
	Output bandwidth	80Mbps	80Mbps	80Mbps
	IPC Input	4CH	8CH	16CH
	Bidirectional Talk	1CH,RCA(Line in,2Vp-p,300ohms)		
Video&Audio output	VGA	1CH,1920×1080,1280×1024,1280×720,1024×768		
	HDMI	1.4a		
		3840×2160,1920×1080,1280×1024,1280×720,1024×768		
Audio Output		1CH,RCA(Line out,2Vp-p,300ohms)		
Video&Audio encoding	Audio Compression	G.711A		
	Audio Bit Rate	8Kbps(16bit)		
Video&Audio decoding	IP channel Resolution	Main stream:Up to 3840×2160 Auxiliary stream:D1		
	Video decoding	H.265 (Main Profile@L5.0 High-tie) / H.264 Up to High Profile@Level5.0)		
	Audio decoding	G.711A,G711U,G726		
	Synchronous Playback	4CH	8CH	16CH
	Decoding Ability	4CH 1080P@30FPS/1CH 4K@30FPS		
Intelligent Analysis		1CH Face detection or 2CH Perimeter detection		
		Up to 1080P		
Other Function	Bidirectional Talk	Two-way voice intercom function		
	Motion Detection	Zones: 396(22*18),Sensitivity: 1~6 (level 6 is highest)		
	Picture Capture	Support JPEG Capture		

HDD Interface	SATA	1 SATA Interface		
	Max Capacity	Unlimited		
POE Interface	POE Interface	4CH	8CH	8CH
		IEEE 802.3AF	IEEE 802.3AF	IEEE 802.3AF
		RJ-45 10/100 Mbps self-adaptive Ethernet interface	RJ-45 10/100 Mbps self-adaptive Ethernet interface	RJ-45 10/100 Mbps self-adaptive Ethernet interface
	Power	≤45W	≤68W	≤68W
External Interface	Network Interface	1 RJ45 10M/100M self-adaptive Ethernet interface		
	USB	2*USB2.0		
Structure	Dimensions	410x293*60mm		
	Front Panel	JN		
	Size	215x235x45mm		
	Weight	0.9KG		
	Installation	Desktop Installation		
General	Power Supply	DC 48V 1.35A	DC 48V 1.875A	DC 48V 1.875A
	Working Temperature	-10°C-- + 55°C		
	Working Humidity	10%--90%		
	Consumption	7W(without HDD)	7W(without HDD)	7W(without HDD)



