

# 8MP 32 CH H265+ NVR

## With Seetong APP and Client



### Features

- The most easy-to-use, popular and commercial 32 channel embedded NVR; specially design for store, small warehouse, office and family, access HD IPC, provide preview, recording, forward and so on functions.
- Support mobile phone monitoring, traversal service, achieve APP seconds connection for preview and remote recording playback, support various network modes:  
IPC – NVR - Seetong Cloud - Seetong Client  
IPC - NVR - Seetong Client  
IPC - NVR - Seetong Cloud - Seetong APP

### Technical parameters

Model No.	SVN-NST832-E2
System Structure	Embedded LINUX design, pure hardware decode, watchdog, hard disk storage, HDMI HD display, IP network video access.
	Main processor Hi3536C
Video Input	HD IPC access, each channel support dual stream access, support auto search, add, recording, preview and without debugging;
	Access bandwidth 128Mbps;
Video Output	1channel HDMI output, support 4K (3840×2160)/30Hz, 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show;
	1 channel VGA output, homology with HDMI, support 1920×1080, 1440×900, 1366×768, 1280×1024, 1280×800, 1024×768 resolution output show;
	Support Seetong client preview, APP preview and seconds connection
	1/2/4/6/8/9/10/16/25/32 pictures real time preview;
Video recording resolution	Support 720P/960P/1080P/3MP/4MP/5MP/4K;
Video Capacity	Support H.265+/H.265/H.264 decoding;
	NVR local recording playback support 4CH 2MP, 2CH 4MP, 1CH 4K; Seetong client recording playback support 4 channels
Audio	Supports one 4 pin 3.5mm audio input and output jack; (1 input 3.3V/1KΩ impedance, 2 output 2.8Vp-p/32Ωmin impedance; 1 GND)
	Standard G.711, support audio and video recording, support HDMI output channel preview and playback audio and video, Seetong client audio and video preview and playback;
Storage	2*SATA hard disk interface, support 8TB capacity;
	Support schedule record, motion detection linkage record
	Support external USB storage devices (such as ordinary U disk, mobile hard disk) backup;
User	Local maximum support for 38 users;

Network Interface	1*RJ45 Ethernet interface, support 10/100/1000M self-adaption; support TCP/IP, IPv4, DHCP, NTP, RTSP,P2P, SMTP, GB28181 and so on protocols;
Peripheral Interface	2*USB2.0 interface(rear); support for the mouse, USB upgrade, import and export;
Front Panel	1* power, 1*record, 1*network indicator light;