

1080P 316L stainless Steel IP68 Underwater Camera



Technical parameters

Model	SVN-S2P-CX5
Resolution	1920*1080
Frame rate	25fps
Lens	2.0mm/2.8mm
Image sensor	HiSilicon + Sony
Certification	IP68 waterproof certification, CE certification
Material	316L stainless steel, corrosion resistant, acid and alkali resistant
Wire rod	Waterproof, corrosion-resistant, acid and alkali resistant, and at the same time can bear the weight of 30KG normal work
Applicable water quality	Sea water, fresh water
Visible distance	Depends on water clarity and turbidity, 0-20 meters.
Waterproof level	IP68 waterproof, 0-50 meters water depth without water ingress
IR LED	White light + infrared, 4pcs high power infrared lamps + 3pcs high power white light lamps; White light lumens: 2.0mm lens - 900 lumens / 2.8mm lens - 600 lumens
Night vision	Black and white in IR lamp mode, color in white lamp mode
Light Adjustment	White light and infrared light can be controlled on/off, 10 levels of light brightness adjustment.Can be controlled by VCR, computer client, APP.According to the actual application environment to switch the light, fine-tuning, to prevent overexposure
Line length	The default cable length is 5 meters, which can be extended to 80 meters upon request. Note: more than 80 meters need special customization
Power supply	12V/2A,24V/2A, Note: Camera tail line shorter than 10 meters with 12V/2A, more than 10 meters: 24V/2A
POE power supply	Support (Note: Camera tail line longer than 10 meters, power supply and POE power supply can only be two choose one.)
Network protocol	IPv4/IPv6,802.1x,ONVIF,HTTPS, HTTP, TCP/IP, UDP, RTP, RTCP, UPNP, RTSP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP,RTSP,ONVIF;SDK Secondary development
Network interface	RJ45 /network port, power port
Dimension	70mm*100mm
Weight	2Kg
Remote monitoring	Support
Client	Support, CMS / Hikvision iVMS-4200
App	Support, APP: umeye pro
NVR	ONVIF protocol, Hikvision, Dahua, Xiongmai, etc.