

Alert Tracking PTZ Camera



Key Features

- Intelligent analysis + panoramic + auto tracking;
- 1 device, 1 Cable, 5 images, 5MP*5=25MP;
- Solution: 5 X SigmaStar377+GC4653(Starlight low illumination);
- Full Color Night Vision
- Fixed lens camera: 6mm/F1.0; Zoom camera: 4.7-94mm (20X optical zoom)
- Rotation speed: 240°/S (High speed dome)
- Built-in Microphone
- Mobile APP for free

PTZ camera feature

- Humanoid Recognition intrusion detection based on AI intelligent analysis.
- Warning line, warning area linkage trigger tracking and zooming
- 4 fixed-focus cameras for 240° panoramic monitoring, 20X zoom PTZ camera Magnified image to detect target details for global detail monitoring
- Support auto tracking function.
- Precision motor drive, professional grade subdivision circuit, support high precision and smooth motion positioning
- IP66 waterproof

Technical parameters

Model	
Model No.	SV509QQLD-NG-BF46D
Camera	
Image Sensor	1/2.8" CMOS
Minimum Illumination	Color: 0.001Lux, B/W: 0.001Lux,0 Lux with IR (Starlight illumination)
3D NDR	Support
WDR	Support
Electronic Shutter	AUTO
Day Night Mode	AUTO ICR Color to B/W
Fixed lens camera	6mm/F1.0
Zoom cam Focal Length	20X Optical zoom, 4.7- 94mm
Zoom Speed	Approx.4s (Optical Wide ~ Tele)
Panoramic field of view	240°
PTZ Angle of View	52°-2.9° (Wide-Tele)
Resolution	2560(H)x2048(V)

Main Stream	2592*1944@25fps, 2500*1600@25fps, 2048x1536@25 fps
Sub Stream	D1@30fps
Video Compression	H.265+/H.265/ H.264
Network protocol	HTTP, TCP/IP, IPv4, DHCP, NTP, RTSP, ONVIF, P2P, PPTP
Interface protocol	ONVIF
APP	AC18Pro / Video-link
PTZ Control	
Warm Light Distance	100M
Horizontal Range	0°~360° continuously
Vertical Range	-5°~90°
Horizontal Speed	0.05°~240°/s
Vertical Speed	0.05°~200°/s
Max Speed	240°/S
Preset	256
Patrol scan	Support
L/R Scan	1pc
Horizontal Scan	1pc
Power-off memory	Support
PARK Action	Watch position/ Area Scan /Horizontal 360°scan/ Cruise
Watch position	Support
General	
Power	DC12V/5A
Consumption	<35W
MountingWall	mounting or lifting
Work environment	temperature: -20~60°C;humidity<90%
Protection level	IP66 waterproof, 6000V lightning protection
Packaging Information	
Single package size	29*29*38m
4 package size	61*61*40cm
Single gross weight	4.2KG
4 package gross weight	17KG

Dimension (Unit: mm)

