

30X Zoom 4K60fps HDMI/USB3.0

12G-SDI/IP Conference Camera



Key Features


- 1/1.8" 4K(3840*2160)@60fps Exmor R CMOS Sensor
- 30X (6.5~195mm) Optical Zoom, 12X Digital Zoom
- 2D/3D noise reduction algorithm, wide dynamic range
- Horizontal rotation: $\pm 170^\circ$, Vertical rotation: $-30^\circ \sim +90^\circ$, Preset: 255
- HDMI: 4K60/50/30/25, 1080P60/50/30/25, 720P60/50;
- Network: 4K60/50/30/25, 1080P30/25, 720P30/25;
- USB3.0: 4K30/25, 1080P30/25, 720P30/25
- RS232, RS485, IP external control interface;
- 12G-SDI: 4K60/50/30/25, 1080P30/25, 720P30/25;
- Network protocols: IPv4, TCP, UDP, HTTP, NTP, DNS, DHCP, ARP, RTSP, RTP, RTCP, RTMP, NDI(Optional), ONVIF, VISCA OVER IP;
- Control interface: RS422 is compatible with RS485, RS232-IN, and RS232-OUT. The RS232 interface supports cascading
- With multi-function infrared remote control, easy to operate.
- Supports VISCA, PELCO-D, and PELCO-P protocols, and supports automatic identification protocols.
- Support auto-tracking, Defog, HDMI audio and video output simultaneously, Image freeze, Preset position cruise,
- Work on Zoom, Facebook, Youtube, SKype, OBS, Potplyer,

Technical parameters

Model	
Model No.	SVN-4K60U30PW
Camera	
Signal system	3840*2160P60/50/30/25, 1080P60/50/30/25, 720P60/50
Image Sensor	1/1.8"8MP Exmor R CMOS Sensor
Scanning mode	progressive
Minimum illumination	Supports ultra-low illumination, 0.1Lux@F1.8 (color)
Shutters	1/30s ~ 1/10000s
White balance	Automatic, Indoor, Outdoor, Manual
BLC	Support
Digital noise reduction	2D&3D Digital noise reduction
Signal-to-noise ratio	≥ 52 dB

Lens	30X Optical zoom
Digital zoom	12X
HOV	59.2°(Wide) ~ 1.98°(Far)
Focal length	F1.8-F3.6, f=6.5-195mm
Horizontal rotation	± 170°
Vertical rotation	-30° ~ +90°
Horizontal rotation speed	1 °/s ~ 100 °/s
Vertical rotation speed	1 °/s ~ 60 °/s
Mirror	Support Horizontal, Vertical
Preset	255
Preset Accuracy	± 0.1°
USB interface	
Video compression	YUV/H.264/ MJPEG
Resolution & Frame Rate	H.264:(3840X2160, 1920×1080, 1280×720, 800*600, 640*480, 704*576, 320*240) 30fps MJPEG:(3840X2160,1920×1080, 1280×720,800*600,640*480,704*576,320*240) 30fps YUV: (1920×1080,1280×720) 30fps
Protocol	UVC1.1 UAC1.0
Control	Support zoom, pan-tilt control, adjustable parameters including brightness, contrast, hue, saturation, sharpness, exposure, focusing.
USB upgrade	Support USB upgrade
I/O interface	
HDMI 2.0	Max 4K60
12G-SDI	Max 4K60
USB 3.0	Max 4K30
Network Encoding	H.265/H.264/MJPEG
Network protocol	IPv4, TCP, UDP, HTTP, NTP, DNS, DHCP, RTSP, RTP, RTCP, RTMP, NDI(Optional),ONVIF, VISCA OVER IP
Communication interface	1 CH RS-232 IN, max. distance: 30 meters, VISCA/Pelco-D/Pelco-P protocol 1 CH RS-422, max. distance: 1200 meters, VISCA/Pelco-D/Pelco-P protocol
Audio interface	Line in X1
Power supply	JEITA Type (DC IN 12V) HEC3800
General	
Input voltage	AC110V-AC220V to DC12V/1.5A
Current	DC12V(DC11.5-DC12.5V)
Operating temperature	0°C ~+45°C
Storage temperature	-10°C ~ +60°C
Power consumption	24W(Max)
Size	178*200*236.5mm
Weight (net)	4KG(3KG)

Interface diagram



1. Lens	6. 12G-SDI Interface	11. LINE IN Interface
2. Camera	7. RS232/RS485 Interface	12. Network Interface
3. Remote Control Receiver, Power Indicator	8. Video format selection switch	13. USB2.0 Interface(Reserve)
4. Mounting screw holes	9. Infrared address jumper switch	14. DC12V Interface
5. Mounting Positioning Holes	10. HDMI Interface	15. USB3.0 Interface
		16. Infrared receiver

Size

