

# 4K IP IR SPEED DOME:SVN-30BA5-4K



- \* Support P2P function
- \* 4.5" body construction,30X optional
- \* Compatible with CMS, UC2,Milestone and AXXON platform
- \* ONVIF2.4 ; Compatible with HIKVISION ,DAHUA, XM,Video park NVR
- \* Intelligent IR illumination & power consumption is variable, dependant the zoom factor

## Specification

### Camera

Sensor	3516AV300 8MP SONY415	
Output Pixel	<a href="#">3840x2160@22fps</a>	
Lens	30X f=4.7mm~141mm	
BLC	Support	
AGC	Auto/manual	
WB	Auto/manual/indoor/outdoor	
DNR	2DNR,3DNR	
WDR	DWDR	WDR≥79dB
S/N Ratio	≥50dB	

### Dome

Communications Protocol	TCP/IP,HTTP,NTP,IGMP,DHCP,UDP,SMTP,RTP,RTSP,ARP,DDNS,DNS,HTTPS,P2P	
Software Control	IE, CMS, Management Platform	
Mobile View(optional)	Support Windows, iPhone platform smartphone	
Video compression	H.265/M-JPEG	
Audio compression	G711,PCM	
Rotation Range	Pan: 0°~360° , Tilt: 0°~93°	
Rotation Speed	Pan: 0~80°/s , Tilt:0~40°/s	
Auto Flip	Horizontal 180° , Vertical 93°	
Preset Points	220pcs presets ( dwell time 01-60s interval available )	
A-B scan	User programmabel(scan speed 1-64 levels setting available)	
Guard Tours	3 groups( Max.16 points, dwell time user selectable)	
Operating temperature	-40°C~+70°C	
Operation menu	English	
Power	DC 12V 3A	
Consumption	≤20W	
Lightning Protection	Transient voltage 6000V	
Related validation	IP66,CE,FCC,RoHs	

### IR parameters

Auto Control IR LED	PWM
IR distance	Up to 120 meters
LEDs	4PCS Array 42Mil IR LED+4PCS Laser LED